



Auracast™ Broadcaster Projects

For TV, Phone, Computer, and Audio Media Center, Supports Bluetooth Core 5.4, PBP v 1.0

Broadcast two audio streams with different configurations to enable a wide variety of receivers. Auracast™ broadcast audio streams can be open for everyone or encrypted for a select audience.

Supported configurations include...

Stereo and mono audio are streamed simultaneously allowing either stereo or mono receiver to be used without switching.

Auracast™ broadcast at 48 kHz, 32 kHz, 24 kHz, or 16 kHz allowing for simultaneously streaming high and standard quality for better interoperability with a wide variety of receivers.



EMSi 5340+USB-C Dongle

Small form factor USB-C dongle that can directly plug into USB-C devices. Included power amplifier for maximum indoor performance. USB Audio from Android Phones/Laptops and PCs (Windows, MacOS and Linux).



EMSi 5340 Module

Splash proof USB Bluetooth® module that supports USB Audio input from Android Phones/ Laptops and PCs (Windows, MacOS and Linux).



IN COLLABORATION WITH





EMSi Audio to LE Audio Bridge

Multiple audio inputs supported. SPDIF, Coaxial, RCA, USB Audio (from Android Phones/Laptops and PCs (Windows, MacOS and Linux) and multiple microphone inputs. Dolby support is possible based on customer request.



Auracast™ Broadcaster

